



|                                     |         |
|-------------------------------------|---------|
| Designation :                       | 32222J2 |
| Principal dimensions(mm)            |         |
| d1 :                                | 110     |
| D :                                 | 200     |
| B :                                 | 56      |
| Basic load ratings(KN)              |         |
| dyc(Cr) :                           | 402     |
| stc(Cor) :                          | 570     |
| Pu :                                | 61      |
| Speed ratings(rpm)                  |         |
| Speed Ratings :                     | 2400    |
| Limiting Speed :                    | 3200    |
| Weight(Kg) :                        | 7,10    |
| ISO335                              |         |
| Dimensions (ABMA) :                 | 3FC     |
| Dimensions (mm)                     |         |
| d :                                 | 110     |
| d1□ :                               | 151     |
| B :                                 | 53      |
| C :                                 | 46      |
| r1,2(min) :                         | 3       |
| r3,4(min) :                         | 2,5     |
| a :                                 | 46      |
| Abutment and fillet dimensions (mm) |         |
| da(max) :                           | 127     |
| db(min) :                           | 122     |
| Da(min) :                           | 170     |
| Da(max) :                           | 188     |
| Db(min) :                           | 190     |
| Ca(min) :                           | 6       |
| Cb(min) :                           | 10      |
| ra(max) :                           | 2,5     |
| rb(max) :                           | 2       |
| Value                               |         |
| e :                                 | 0,43    |
| Y :                                 | 1,4     |
| Yo :                                | 0,8     |