



|                                     |          |
|-------------------------------------|----------|
| Designation :                       | 32317BJ2 |
| Principal dimensions(mm)            |          |
| d1 :                                | 85       |
| D :                                 | 180      |
| B :                                 | 63,5     |
| Basic load ratings(KN)              |          |
| dyc(Cr) :                           | 391      |
| stc(Cor) :                          | 560      |
| Pu :                                | 62       |
| Speed ratings(rpm)                  |          |
| Speed Ratings :                     | 2800     |
| Limiting Speed :                    | 4000     |
| Weight(Kg) :                        | 7,50     |
| ISO335                              |          |
| Dimensions (ABMA) :                 | 5GD      |
| Dimensions (mm)                     |          |
| d :                                 | 85       |
| d1□ :                               | 135      |
| B :                                 | 60       |
| C :                                 | 49       |
| r1,2(min) :                         | 4        |
| r3,4(min) :                         | 3        |
| a :                                 | 52       |
| Abutment and fillet dimensions (mm) |          |
| da(max) :                           | 102      |
| db(min) :                           | 99       |
| Da(min) :                           | 138      |
| Da(max) :                           | 166      |
| Db(min) :                           | 169      |
| Ca(min) :                           | 7        |
| Cb(min) :                           | 14,5     |
| ra(max) :                           | 3        |
| rb(max) :                           | 2,5      |
| Value                               |          |
| e :                                 | 0,54     |
| Y :                                 | 1,1      |
| Yo :                                | 0,6      |